

INDUSTRIAL FLOORS

PROCEDURE

Durch das spezielle Verfahren entsteht der einzigartige ökologische GreenLINE Floor

- 1. Grinding:** This work step is the basis for a surface treatment of cementitious floors. In the case of renovation, the treatment can be carried out during production and is dust-free.
- 2. Finishing:** The basis for the resistance of the floor to aggressive media, is produced by mineral impregnation.
- 3. Polishing:** Polishing produces the visually sophisticated and above all dust-free, easy to clean and slip-resistant surface of the floors.

PROPERTIES

Technical properties of GreenLINE Floor

Look: Depending on the grinding depth, the floor gets a terrazzo look. The surface is shiny.

Anti-slip class (R-class): GreenLINE Floor floors have a classification in the R9 range. R9 class is required in public buildings.

Ingredients: Concrete floor: as the basic product is a concrete according to customer requirements and local conditions, the ingredients of the floor are largely determined by the concrete used.

Impregnations: Potassium methylsilane triolate, water, organic components.

unique
permanent
inexpensive



TECHNICAL PROPERTIES OF GREENLINE FLOOR

LOOKS

Depending on the grinding depth the floor gets a terrazzo look. The surface is shiny.

ANTI-SLIP CLASS (R-CLASS)

GreenLINE Floor floors have a **classification in the area R9**. R9 class is required in public buildings.

INGREDIENTS

Concrete floor: Since the starting product is a concrete according to customer requirements and local conditions, the ingredients of the floor are largely determined by the type of concrete used.

Impregnations: Potassium methylsilane triolate, water, organic components.

FLAMMABILITY

The floor is not combustible. Extinguishing agents and fire-fighting measures must be adapted to the type of building / surrounding fire.

LIFETIME

With appropriate care according to care instructions unlimited stock.

RESISTANCES

- Oils
- Lyes
- Acids

CLEANING

Cleaning with automatic cleaning machines and **GreenLINE Polish Pad 1 oder 2**. Manual cleaning with mops. Neutral and alkaline cleaners are permissible as cleaning agents.

EXCELLENT

GreenLINE Floor was awarded the "Industry Award Best of". in 2015 and 2018.



BEST OF



BEST OF